



NEW TECHNOLOGY. ENDURING VALUES.

What happens when you incorporate new technology and yet retain the values you've always appreciated in a car?

You get a car that combines sturdiness with speed, reliability with power, luxury with space and agility with safety. A car like the Ambassador 1800 LSZ. With a new power-packed 1817 cc ISUZU engine, setting standards in performance and comfort. Come, experience the difference.



1 Standard model. All models shown. Prices, with an Option, to other
models in the Isuzu Ambassador range. © 1997 Isuzu Motors, Inc.

1 Standard model. All models shown. Prices, with an Option, to other
models in the Isuzu Ambassador range. © 1997 Isuzu Motors, Inc.

SPECIFICATIONS

ENGINE :	
Type	4 Cyl. In-line OHV 16V
Capacity	1810 CC
Bore x Stroke	84.08 x 80 mm
Compression Ratio	8.5 : 1
Max. Power @ (RPM)	74 BHP @ 5000 + 5000
Max. Torque (kg-m)	135 @ 3000 + 3000
Coolant	Water cooled

TRANSMISSION :

Coupling	Dry Disc (Decoupled to 3 main shafts)
Gear Box	5 Speed manual; 3 speed gear box having overdrive
Gear Ratios	1.00 : 1.176 : 1.344 : 1.600 : 2.075 : 2.440
Front Drive Ratio	1.00
Front	Front
Rear	Rear

SUSPENSION :

Front	Independent suspension with coil springs and A bar with hydro-leaf shock absorbers among shock absorbers
Rear	Coil-sprung leaf springs with hydro-leaf shock absorbers among shock absorbers
STEERING :	Hand Rack & Pinion

Type	Overall Height
	2250 ± 10 mm

TIRES & TYRES :

Service	Service related dual circular hydraulic F/T tires with hub caps in 18x5.5 + 18x6.5 inches.
Turning Circle Dia.	10.25 mtrs.
Brakes :	Service
Front	Surge related dual circular hydraulic F/T tires with hub caps in 18x5.5 + 18x6.5 inches.
Rear	Surge related dual circular hydraulic F/T tires with hub caps in 18x5.5 + 18x6.5 inches.

WHEELS :

Type	Disc
No. of Doors	4
Front Track	1490 ± 15 ± 6 mm (Crossed)
Rear Track	1490 ± 15 ± 6 mm (Crossed)

BODY :

Type	Unisted
No. of Doors	4
Front Track	1490 ± 15 ± 6 mm (Crossed)
Rear Track	1490 ± 15 ± 6 mm (Crossed)

ELECTRICALS :

Battery	12V 45 Ah, lead acid.
Alternator	12V 45A
FUEL CAPACITY :	54 liters.
Level (Overall)	4750
Width (Overall)	1475
Height (Overall)	1650
Wheelbase	2444
Wheelbase	1474 mm
GVM	1054 kg



Deep plating around to prevent rusting and enhance body life.

- Specifications are subject to change without notice.
- Ambassador 1500 LSZ is one of the most fuel efficient sedans.



HMT TECHNOLOGY BRINGS VALUES.